



SeekTech® SR-60 Locator

For the fastest, easiest, most versatile receiver available.

Versatility

- Can trace any frequency from 10 Hz to 93.000 Hz.
- Can trace energized lines and sondes (active beacons) simultaneously.
- Has all the ease of use and accuracy of the SR-20 locator but with ALL locatable frequencies. Choose the SR-60 locator for fast confident locates even under tough locate conditions (poor conductors, poor soil conditions, poor grounding, etc.).

SR-60 Locator Specifications

Active Line Trace Frequencies**	128 Hz, 1 kHz, 8 kHz, 33 kHz, 51 kHz, 93 kHz.
Passive Power Trace	.50 Hz, 60 Hz, <4 kHz Broadband.
Passive Radio Trace	.4 kHz - 15 kHz, 15 kHz - 36 kHz.
Sonde Frequencies**	.16 Hz, 512 Hz, 640 Hz, 850 Hz, 8 kHz, 16 kHz, 33 kHz.
Power Source	4 C-Cell Batteries.
Battery Life	Approximately 16 Hours.
Weight	.5.1 lbs. (2.3 kg).
Meets FCC Class A and EN 55022 Class A requirements.	

** 30 user definable frequencies can be set from 10 Hz to 93.000 Hz.

Standard Equipment

- Hard plastic carrying case.
- Surface markers and clip.
- Instructional DVD.
- Operator's manual.
- 4 C-Cell Batteries (alkaline).

Ordering Information

Catalog No.	Description	Weight	
		lb.	kg
30123	SeekTech SR-60 Line Locator	5.1	2.3
29798	SR-60 Case	5	2.2

