

Part No.

QTHP-4FBA-RG

5kpsi / 35 MPa Hydraulic hand pump, 2 Quick-test outlet ports, 3 ft hose, 1/4" MNPT Process conn. 5kpsi / 35 MPa Hydraulic hand pump, 2 Quick-test outlet ports, 1 m hose, 1/2" FBSPP gauge conn., 1/4" FBSPP Process conn.

5kpsi / 35 MPa Hydraulic hand pump, 2 Quick-test outlet ports, 1 m hose, 1/2" FBSPP gauge conn., 1/4" FBSPP Process conn.



QTHP-4FBA-RG

Included Items

- Hand Pump - QTHP Hydraulic Hand Pump (QTHP)
- Reference Connection - G 1/2" female BSPP (ISO 228/1) x female Quick-test, no check-valve, brass (QTHA-4FBA-RG)
- Hose - Quick-test 6900 psi hose, brass hose ends, 1 m (3.3 ft) long (QTQT-HOS-1m)
- Process Connection - G 1/4" female BSPP (ISO 228/1) x male Quick-test, no check-valve, brass (QTHA-2FB0-RG)

Specs/Attributes

Hose 1	Quick-test Hose, Stainless Steel ends, 1m long
Process Connection	1/4" Female BSPP (G1/4)
Reference Connection	1/2" Female BSPP (G1/2)
Weight	54 oz / 3.38 lbs / 1.53 kg
Dimensions	H: 5.7 in (14.48 cm) x W: 6 in (15.24 cm) x D: 8.6 in (21.84 cm)

Hand Pump QTHP

Materials	Anodized Aluminum, Brass, Stainless Steel
Max Pressure	5000 PSI / 345 bar / 35 MPa
Media Compatibility	Petroleum Based Oil, Water
Seal Materials	Buna-N, Teflon

Hand Pump QTHP

Fine Adjustment Resolution	0 PSI / 0 mbar / 0.00 kPa
Weight	46.9 oz / 2.93 lbs / 1.33 kg
Dimensions	H: 5.7 in (14.48 cm) x W: 6 in (15.24 cm) x D: 10.6 in (26.92 cm)

Reference Connection QTHA-4FBA-RG

Has Check Valve	No
Materials	Brass
Max Pressure	5000 PSI / 345 bar / 35 MPa
Max Temperature	225 °F / 105 °C
Max Vacuum	0.00 In Hg / 0.00 mm Hg
Min Temperature	0 °F / -18 °C
Wrench Size	1-1/16 In 27 mm
Dimensions	H: 1.76 in (4.47 cm) x W: 1.06 in (2.69 cm)

Hose QTQT-HOS-1m

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Inner Diameter	0.08 In / 3.00 mm
Length	1.00 m / 3 ft 3 in
Materials	Brass
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Temperature	140 °F / 60 °C
Max Vacuum	0.00 In Hg / 0.00 mm Hg
Min Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT

Process Connection QTHA-2FB0-RG

Has Check Valve	No
Materials	Brass
Max Pressure	5000 PSI / 345 bar / 35 MPa
Max Temperature	225 °F / 105 °C
Max Vacuum	0.00 In Hg / 0.00 mm Hg
Seal Materials	Buna-N
Wrench Size	3/4 In 19 mm
Dimensions	H: 1.12 in (2.84 cm) x W: 0.75 in (1.91 cm)