


Conductivity Standards and Accessories


Approximate Cell Constant	Cell Material	Dimensions	Min/Max Immersion
0.475 cm ⁻¹	Epoxy/Graphite	Dia - 15 mm Length - 120 mm	35/NA mm
0.55 cm ⁻¹	Epoxy/Graphite	Dia - 12 mm Length- 120 mm	35/NA mm
0.475 cm ⁻¹	Epoxy/Graphite	Dia - 15 mm Length - 120 mm	35/NA mm
0.55 cm ⁻¹	Epoxy/Graphite	Dia - 12 mm Length- 120 mm	35/NA mm

Approximate Cell Constant	Cell Material	Dimensions	Min/Max Immersion
0.1 cm ⁻¹	Steel, V4A	Dia - 13 mm Length - 120 mm Flow Cell Volume 8-12 mL	35/110 mm
1.0 cm ⁻¹	Epoxy/Graphite	Dia - 18 mm Length - 134 mm	35/NA mm
10 cm ⁻¹	Glass/Platinum, Platinized	Dia - 16 mm Length - 115 mm	55/110 mm
1.0 cm ⁻¹	Epoxy/Platinum, Platinized	Dia - 12 mm Length - 120 mm	20/90 mm
0.1 cm ⁻¹	Glass/Platinum, platinized	Tip Dia - 17 mm Tip Length - 22 mm Dia - 13 mm Length - 120 mm	25/120 mm
1.0 cm ⁻¹	Glass/Platinum, Platinized	Dia - 13 mm Length - 120 mm	25/120 mm
1.0 cm ⁻¹	Epoxy/Steel	Dia - 13 mm Length - 120 mm	25/120 mm


Cat. No.	Description
011008	100 µS/cm conductivity/TDS standard, 5 x 60 mL
01100910	147 µS/cm conductivity standard, 10 pouches
011007	1413 µS/cm conductivity/TDS standard, 5 x 60 mL
01100710	1413 µS/cm conductivity/TDS standard, 10 pouches
011006	12.9 mS/cm conductivity/TDS standard, 5 x 60 mL
01100610	12.9 mS/cm conductivity/TDS standard, 10 pouches
011005	111 mS/cm conductivity standard, 5 x 60 mL
01100510	111 mS/cm conductivity standard, 10 pouches
990106	0.1 M KCl conductivity standard, 475 mL
1010001	Conductivity calibration resistor kit for Orion Star Series conductivity meters, MiniDIN
011220	Conductivity calibration resistor kit for 105A ⁺ , 115A ⁺ , 125A ⁺ , 145A ⁺ , and 150A ⁺ meters, 8 Pin DIN
011221	Conductivity calibration resistor kit for 130A, 131S, 135A, 136S, 162A, 550A, and 555A meters, 8 Pin Waterproof DIN
011001	Conditioning solution for 011050, 011050A, and 011050MD conductivity cells
0105PK	Platinizing kit, includes fixture and solutions
010010	Platinizing solution and vessel
013017	Replacement flow cell for 013016A, 013016D, and 013016MD
013045	Stainless steel protective probe guard (for 013005MD, 013010MD, 013025MD, 013005A, 013010A, 013030A, 013060A, 013005D, 013010D)
080045	Stainless steel and plastic protective probe guard (for 013005MD, 013010MD, 013025MD, 013005A, 013010A, 013030A, 013060A, 013005D, 013010D)
081045	Plastic protective probe guard (for 013005MD, 013010MD, 013025MD, 013005A, 013010A, 013030A, 013060A, 013005D, 013010D)



MiniDIN



8 Pin DIN



WP 8 Pin DIN



2.5 mm phono Jack

Key Information

A). MiniDIN connector (Star) **B).** 8 Pin DIN connector (A+ Series) **F).** 8 Pin Waterproof DIN connector (A Series) **H).** BNC and 2.5 mm Phono Jack connector (Russell)

* Conductivity cell does not have temperature compensation

** 3-Electrode Conductivity Cell