



Portable Flow Meter

9301

Portable Flow Meter

- A technologically advanced flow and pressure meter with stainless steel paddle wheel
- Solid state electronics with no moving parts to adjust
- Includes a heavy-duty storage case, 12V internal battery, 110V AC battery charger, 12V DC auto power supply cord
- 2 1/2" (65 mm) female swivel
- Maximum flow 1250 gpm (4800 lpm) through 2 1/2" (65 mm) sensor body
- Width: 20 1/2" (520.7 mm), height: 17 1/2" (444.5 mm), depth: 8 1/2" (215.9 mm)
- Weight: 30 lbs (13.6 kg)
- See page 185 Technical Data section for more details regarding flow meter set up



Style 9301

Hose Test Valve

2285

Hose Tester Gate Valve

Meets NFPA 1962 requirements for testing hose with fire apparatus.
Includes 1/4" hole in gate for maintaining test pressure at low volume.

Style	Material	Size	Length	Weight lbs. (kg)	Inlet	Outlet	Number Of Turns
2285	Pyrolite®	2 1/2" (65 mm)	5 1/2" (140 mm)	4 (1.8 kg)	2 1/2" (65 mm)	2 1/2" (65 mm)	21



Style 2285
Hose Gate Valve

Apparatus Test Gauge Kit

ATGK-3

- Same as ATGK-2 with a space for an extra gauge to be mounted



ATGK-3

Pressure/Vacuum Panel Adapter

44

Pressure/Vacuum Panel Adapter

- Complete fitting for pump panel
- Simplifies attachment of gauges for pump tests
- Remove hex plugs and screw in gauges
- Length: 3 1/2" (89 mm), height: 1 3/8" (35 mm), weight: 8 oz.



Style 44