

BESANTEK 2 in 1 Digital Coating Thickness Meter, is designed for measurement of ferromagnetic metal base (iron, nickel, etc.) and non ferromagnetic metal base (aluminum, brass, stainless steel, etc.).

Features:

- Integrated 2 in 1 probe.
- Automatic F/NF detection and display of the substrate type.
- Continuous and single measurement available.
- Simultaneously display measuring value, average value, max. value, min. value & standard deviation.
- Auto calibration and auto zero adjustment.
- 50 groups of data.
- Brightness adjustable backlight.
- Automatic power on and off.
- Metric & imperial measurement systems.
- Ideal for use in control of painting, distinguishing crashed cars, etc.
- Set higher and lower alarm range for measuring.
- Low battery warning indicator.
- TFT 320 x 240 LCD display.
- Accessories: Instruction manual, Fe/NFe probes, set of plastic test shims and 2 reference calibration plates (steel and aluminum), hard shell storage case and batteries.



BST-CTG04

Technical Specification:

BST-CTG04	
Measuring Range	0~1250μm, 0~50mils (max. 2000μm/80mils for reference)
Resolution	1μm, 0.1mils
Accuracy	±(2μm+2%) or ±(0.1mils+2%)
Surface Curvature	Convex 1.5mm/concave 7mm
Minimum Test Surface	Ø8mm
Minimum thickness of	0.4mm
Response Times	0.6sec
Probe Length	Approx. 93cm
Operating Temperature	-10~50°C (12~122°F)
Power Source	1.5V AAA battery x 2
Dimensions	166 x 68 x 30 mm
Weight	Approx. 180g (batteries included)

Accessories



Ordering Information:

- BST-CTG04: 2 in 1 Digital Coating Thickness Gauge with Probe.